



CORROSION INHIBITING VpCI® POWDERS



CorroLogic® Powder Corrosion Inhibiting Powder for Soil Side Corrosion



- continuous redeposition.
- Does not contain silicates, phosphates, nitrites or heavy metals
- No surface preparation is required
- Provides liquid, vapor and interface protection (above the liquid level)

DOSAGE AND APPLICATION METHOD

Apply powder by fogging with Corrologic® pneumatic equipment through the tank floor.

Recommended dosage and location of injection ports depends on multiple factors such as tank foundation design, environmental conditions and design life.

Consult with Cortec® Corrosion Engineering and Field Services for system recommendation.

PRODUCT DESCRIPTION

Corrologic® Powder is a Vapor phase Corrosion Inhibitor (VpCI®) powder designed for the protection of aboveground storage tanks bottom plates against the detrimental effects of soil-side corrosion. When introduced into the under-tank environment, VpCI® molecules sublime from the powder, diffuse through the sand pad to the tank floor creating a monomolecular protective layer even in hard-to-reach areas.

Corrologic® Powder is designed for corrosion mitigation for tanks with or without cathodic protection (CP). For CP-protected tanks, Corrologic® protects areas where current cannot reach such as air gaps, shielded zones and where sand is dry.

Corrologic® Powder is typically fogged through the tank floor when tank is out of service for testing and inspection.

FEATURES

- Migrates through different qualities of sand
- Creates monomolecular inhibiting layer with self replenishment properties
- Vapor phase inhibiting action protects inaccessible and recessed surfaces
- Provides effective protection against pitting corrosion
- Concentrated formula with enhanced flowability for ease of application
- If disturbed by moisture or fluid flow, the layer is replenished by

TANKS PROTECTED

- Existing tanks out of service
- CP protected tanks
- Non-CP protected tanks

TYPICAL PROPERTIES

Appearance	White
pH	6-7 (1% aqueous)
Solubility in Water at 20°C	< 1%

PACKAGING AND STORAGE

Corrologic® Powder is available in 5 pounds (2.3kg), 50 pound (23Kg) and 100 pound (45Kg) lined drums. Store in a sealed container in a dry warehouse avoiding direct exposure to sunlight, with a temperature not exceeding 150°F (65°F). Shelf life is up to 24 months.



**FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



CORTEC
CORPORATION

Environmentally Safe VpCI®/MCI® Technologies

Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 10/14/16. Supersedes: 08/22/16. ©Cortec Corporation 2002-2016 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2016, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.